

Technical Data Sheet



INTERIOR SUPER

Product Characteristics

A water-based painter's color based on acrylate dispersion comprising fillers, additives, fungicides, cellulose derivative and titanium white.

Specific Qualities

The outstanding feature of Rokointerior Super paint is its superior covering power: one coat is usually enough. It has extreme sparkling whiteness, up to 96 %. It is also easily treatable, and doesn't brittle, crack or peel off. It is washable, resistant to dry abrasion and vapor permeable.

Application

Interior Super paint is recommended for painting of rooms for demanding clients. Ideal for offices, prestige premises etc. Being very universal, it can be applied on coating plaster boards, old and new internal plasters, concrete chipboard and fiberboard

Treatment Instructions

Paint application:	by brush, roller coating, spraying (airless)
Thinning:	by water (acc. to requirements)
Tool cleaning:	by water immediately after coating
Non -volatiles:	min. 62 %
Consumption:	150 - 200 g/m ² (for one coat)
Drying:	after every coat layer approx.. 2-4 h (acc. to temperature and rel. humidity)
Discharge time F6/23 °C:	min. 65 s

Technical Data

Binder:	acrylate dispersion
Specific gravity:	min. 1.45 g/ccm
Flash point:	nonflammable
Difussion resistance:	sd < 0.14 m ČSN 73 25 80
Gloss degree:	mat max. 2.6 (refractometer 60 degrees)
Shelf life:	2 years in reliably closed containers at +5 up to +25 °C

Technical Data Sheet

Coating Process:

Preparation

The surface has to be clean, dry and dust-free. Very dirty surface is to be scraped off thoroughly. If the surface suffers from mildew attack, treat it first by a product such as Fungisane. New lime-cement and new plasters should first mature properly for at least 3 weeks (acc. to weather).

Primer coat:

This is necessary where there are old disintegrated plaster boards, where absorbent grounds have to be filled-in, or where it is necessary to increase adhesion.

Application:

- a) 1x the ROKOLATEX PLUS primer agent (to be diluted by 4 parts of water: 1 part of ROKOLATEX PLUS),
- b) where the surface isn't too problematic, 1x INTERIOR SUPER(1 part of paint : 2 -3 parts of water.)

Top coat:

(Only where the required hiding power cannot be reached by the primer coat)

1x INTERIOR SUPER diluted by approx..5 % water.

CAUTION:

Safety instructions: Don't eat, drink or smoke while working with the product. Protect the eyes and skin against contamination from the paint. The paint is strongly alkaline. If eyes are affected, rinse immediately with clean water and seek medical advice.

Notice:

Information stated in this datasheet is intended only for advisory purposes and is not exhaustive. In the case you are going to use the paint for a purpose different from that described here, first ask for a written statement.

Without this statement we will bear no responsibility for the paint quality and/or losses and damages given by any incorrect application. In addition, we also refer to our Trading Conditions.

Page 2 (total 2)	Rokospol a.s., závod Kaňovice č. 101, 76341, tel. – 577 110 132-3, fax – 577 110 136, e-mail:rokospol@rokospol.cz, http://www.rokospol.com	Actualization: PR 08.12.2014
---------------------	--	---------------------------------